

MICRO

PAN & TILT CAMERA



**MICRO PAN & TILT CAMERA
WITH THE LATERAL & MAINLINE PROBE**

The CUES Micro Pan & Tilt Camera is designed to navigate through multiple wyes and 45 and 90 degree bends / sweeps with the integrated directional rod.

All pan and tilt functionality is integrated into the systems' controller. The Micro Pan & Tilt Camera includes a detachable steering wand, self-leveling camera head, built-in lens wiper, 360 degrees pan and tilt, (2) banks of LED's with variable light intensity, and a built-in sonde with switchable frequencies.



**LAMP II shown with
MICRO P&T Camera**

Use the optional CUES Micro Pan & Tilt Camera with the CUES LAMP II for pipe inspections.

MICRO PAN & TILT CAMERA Features & Benefits

- Rotation: Continuous 360 degree rotation; Pan: Continuous 360 degree rotation.
- Illumination: White LED Lighting.
- Scratch-resistant sapphire window.
- Ability to direct the camera and lights to observe all defects, including joint separations, cracks, offsets, spotting, and roots.
- Built-in multi-frequency sonde transmitter; 512 Hz or 8 kHz.
- Detachable steering wand provides the ability to navigate through multiple wyes.
- Built-in lens wiper.
- Self-leveling camera head.
- LED lighting with variable intensity.
- Rugged carrying case.



Built-in multi-frequency sonde transmitter; 512 Hz or 8 kHz.

Direct the camera and lights to observe all pipeline defects.

Built-in camera lens wiper; no need to remove the camera from the pipe to clean the lens.

Detachable steering wand to navigate through multiple wyes.